# **POS457**

## Flex to fit your space

A beautifully designed die-casting POS solution. With the ability to shift between a desktop POS and a wall-mounted POS, the POS457 will transform your customer experience. With a range of peripheral modules including MSR, iButton and secondary display, the POS457 is the perfect choice for the retail and hospitality environment.



## System



#### **Processor**

Intel® Celeron J6412 Intel® Core i3-1115G4 Intel® Core i5-1135G7



#### **Supported OS**

Windows 10 IoT Enterprise, Linux



#### Storage

128GB M.2 SSD (Celeron) 256GB M.2 SSD (i3/i5)



### Memory

8GB DDR4 RAM

### I/O Ports



#### **USB**

3 x USB 3.0, 3 x USB 2.0, 1 x Powered USB 12V, 1 x Powered USB 24V



#### **Cash drawer**

1 x RJ11



#### **Serial port**

2 x DB9



#### LAN

1 x RJ45



#### DC jack

1 × 4 pin w/latch

## Certification








Protecting the planet together...









Committed to compliance with care ISO 14001

## Here's the detail...

System	Motherboard	F34	F84U
	Processor	Intel® Celeron J6412	Intel® Core i3-1 1115G4 / i5-1135G7
	Memory	8GB DDR4	
	Storage	128GB M.2 SSD	256GB M.2 SSD
	Supported OS	Windows 10 IoT Enterprise, Linux	
Displays	Size & resolution	15.6" 1920×1080 True-Flat PCAP multi-touch	
	Touch screen		
I/O ports	USB Type-A	2 x USB 3.0, 2 x USB 2.0 1 x USB 2.0 (data only), 1 x USB 3.0 (data only) 1 × 12V, 1 × 24V	
	USB Type-C		
	Powered USB		
	Serial port		2 x DB9
	LAN	1	I x RJ45
	Cash drawer		1 x RJ11
	DC jack	1 × 4	4 pin w/lock
Power	Power supply	65W / 19V (120W/19V with PUSB 12V & 24	120W / 19V 4V)
Certificate	EMC & safety	F	FCC Class A, CE Mark, LVD
Environment	Operating tempera	ture	0°C ~ 35°C (32°F ~ 95°F)
	Storage temperatu	re -2	20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20	% ~ 85% RH non-condensing
Dimensions	WxDxH	369 × 20	09 × 264 mm (14.5" x 8.2" x 10.4")

PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE

Protecting the planet together...









BOXTEC

Management compliance with ISO 14001