

Ninja 667N2





The next generation of POS



We've taken the everything you love about the Ninja 667 - the sleek design, multiple counter configurations, and ease of maintenance - and combined it with the latest Intel® technology.


The result? The next generation of POS terminal. The Ninja 667N2 uses cutting-edge features to take your customer experience to the next level, while maintaining the reliability you expect from our products.

System

-  **Motherboard**
F14 / F34 / F84U
-  **Screen sizes**
11.6" wide / 15.6" wide / 15.1" square
-  **Storage**
64G eMMC / 256G M.2 SSD
-  **Memory**
up to 16GB RAM



Certification



Protecting the planet together...



Committed to environmental care



Environmental Management compliance with ISO 14001



Community and Social Responsibility



Here's the detail...

System	Motherboard	F14	F34	F84U
	Processor	Qualcomm® 450	Intel® Elkhart Lake Celeron J6412	Intel® Tiger Lake i5-1135G7
	Memory	3GB LPDDR3	8GB DDR4 (up to 16GB)	
	Storage	32GB eMMC	128GB SSD	256GB SSD
	Supported OS	Android 10	Windows 10 IoT, Linux	
I/O ports (front side)	USB type-A		1 x USB2.0	
I/O ports (rear side)	USB type-A		2 x USB 3.0 2 x USB 2.0	
	USB type-C	1 x USB 3.0 (data only)	1 x USB 2.0 (data only) 1 x USB 3.0 (data only)	1 x USB 3.0 (data only) 1 x USB 3.0 (full)
	Micro USB	1	-	-
	FeDP		2 x Flytech proprietary Mini-DP	
	Serial port	2x DB9 (powered RS232) (default 0V; COM1, COM2 0V/5V/12V)		
	LAN		1 x RJ45	
	Cash drawer		1 x RJ11	
Audio	Speaker		1 x 3W	
Display	LCD size		15.6" (16:9)	
	Resolution		1920×1080	
	Touch screen		True-Flat PCAP multi-touch	
Power	Power supply		65W/19V	120W / 19V
Comms	WLAN + BT	BT4.1 WiFi 802.11 b/g/n/ac	WiFi+BT USB dongle (option)	
Certificate	EMC & safety	FCC Class A, CE Mark Class A, LVD		
Environment	Sealing		IP54 (front side)	
	Operating temperature		0°C ~ 35°C (32°F ~ 95°F)	
	Storage temperature		-20°C ~ 60°C (-4°F ~ 140°F)	
	Humidity		20% ~ 85% RH non-condensing	
Dimensions	W x D x H	375.8 × 200.0 × 374.7mm (with stand and plate)		

Peripheral options

MSR	-	3-Track MSR (USB)
Fingerprint	-	Fingerprint reader (USB)
NFC	-	NFC reader
iButton	-	iButton (USB)
Scanner	-	2D scanner
Customer display	-	LCM display 2 × 20 characters (USB)
2nd display	-	11.6" & 15.6" 2nd display
Powered USB box	-	2 × 12V powered USB 1 × 24V Powered USB

Accessory options

Cable	-	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI
Thermal solution	-	Heatsink kit

PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE